



**Home Innovation**  
NGBS GREEN CERTIFIED™

THIS SIGNIFIES THE FOLLOWING CONSTRUCTION PRODUCTS

**VIANCE PRESERVE (CA) PRESSURE TREATED LUMBER**

MANUFACTURED BY

**VIANCE LLC**

ARE CERTIFIED FOR POINTS TOWARD NGBS GREEN CERTIFICATION TO THE  
ICC-700 NATIONAL GREEN BUILDING STANDARD, AS DETAILED BELOW.

  
Michael Luzier – President & CEO

March 1, 2013  
Approval Date

December 31, 2022  
Expiration Date

**CERTIFICATE #000220**

This certificate is not a representation, warranty, or guarantee of product performance or certification of code compliance. For details of the product warranty, consult the product manufacturer.



NGBS Green Certificate #NGBSGCP-000220

Products: Viance Preserve (CA) Pressure Treated Lumber

Manufacturer: Viance LLC

The product(s) shown on this report have been independently verified as eligible products for use in achieving points toward project certification under ICC-700 National Green Building Standard. Home Innovation Research Labs authorizes accredited verifiers to award points toward certification without additional documentation when the product(s) is used as noted below.

<b>2012 NATIONAL GREEN BUILDING STANDARD</b>			
<b>PRACTICE #</b>	<b>PRACTICE DESCRIPTION</b>	<b>POTENTIAL POINTS AVAILABLE</b>	<b>ADDITIONAL CONDITIONS OF USE TO AWARD POINTS</b>
2012 NGBS 503.2(4)	Erosion reduced through use of terracing, retaining walls, landscaping and restabilization.	5	Retaining walls built with this product must be an integral part of the installed landscape plan designed to limit long-term erosion.
2012 NGBS 602.1.6	Termite-resistant materials are used in portions of the building.	2-6	To earn 2 points, product is used in conjunction with other termite-resistant materials for the first 2' of all the foundation, floor, and structural wall, wall cladding, and exterior deck components in zones with slight to moderate termite infestation. Four points are awarded when used in the first 3' in moderate to heavy termite zones, and 6 points are awarded for use in all of the foundation, floor, and structural wall, wall cladding, and exterior deck components in areas of very heavy termites.

<b>2015 NATIONAL GREEN BUILDING STANDARD</b>			
<b>PRACTICE #</b>	<b>PRACTICE DESCRIPTION</b>	<b>POTENTIAL POINTS AVAILABLE</b>	<b>ADDITIONAL CONDITIONS OF USE TO AWARD POINTS</b>
2015 NGBS 503.2(4)	Erosion reduced through use of terracing, retaining walls, landscaping and restabilization.	6	Retaining walls built with this product must be an integral part of the installed landscape plan designed to limit long-term erosion.
2015 NGBS 602.1.6	Termite-resistant materials are used in portions of the building.	2-6	To earn 2 points, product is used in conjunction with other termite-resistant materials for the first 2' of all the foundation, floor, and structural wall, wall cladding, and exterior deck components in zones with slight to moderate termite infestation. Four points are awarded when used in the first 3' in moderate to heavy termite zones, and 6 points are awarded for use in all of the foundation, floor, and structural wall, wall cladding, and exterior deck components in areas of very heavy termites.

2020 NATIONAL GREEN BUILDING STANDARD			
PRACTICE #	PRACTICE DESCRIPTION	POTENTIAL POINTS AVAILABLE	ADDITIONAL CONDITIONS OF USE TO AWARD POINTS
2020 NGBS 503.2(4)	Erosion reduced through use of terracing, retaining walls, landscaping and restabilization.	6	Retaining walls built with this product must be an integral part of the installed landscape plan designed to limit long-term erosion.
2020 NGBS 602.1.6	Termite-resistant materials are used in portions of the building.	2-6	To earn 2 points, product is used in conjunction with other termite-resistant materials for the first 2' of all the foundation, floor, and structural wall, wall cladding, and exterior deck components in zones with slight to moderate termite infestation. Four points are awarded when used in the first 3' in moderate to heavy termite zones, and 6 points are awarded for use in all of the foundation, floor, and structural wall, wall cladding, and exterior deck components in areas of very heavy termites.